



GRIPTO	608 / 608 LP	609 / 609 LP	708	709
Attaching	flange	flange	flange	flange
Max outreach	7,8 m	8,5 m	7,8 m	8,5 m
Length of main boom	2,65 m	3,35 m	2,65 m	3,35 m
Length of extension boom	2x1,6 m	2x1,6 m	2x1,6 m	2x1,6 m
Height	1,9 m	1,9 m	1,9 m	1,9 m
Width	1,25 m	1,25 m	1,25 m	1,25 m
Lifting moment, brutto/netto (4 m)	62/40 kNm	62/37 kNm	75/51 kNm	75/47 kNm
Allowable load (without grapple and rotator)	1020 kg/4m	930 kg/4m	1290 kg/4m	1190 kg/4m
Turning angle of boom	380 degrees	380 degrees	380 degrees	380 degrees
Turning moment, brutto	20 kNm	20 kNm	20 kNm	20 kNm
Lubrication of turning device	oil	oil	oil	oil
Cylinders in turning device	4	4	4	4
Weight, basic loader	1150 kg	1180 kg	1170 kg	1200 kg
Working pressure (low pressure)	210 (185) bar	210 (185) bar	210 bar	210 bar
Recommended pump output	80-120 l/min	80-120 l/min	80-120 l/min	80-120 l/min

Recommended rotator: Indexator GV6

Recommended grapple: Kronos 0,26

Grapple size	0,26 m ²	0,26 m ²	0,26 m ²	0,26 m ²
Max opening of grapple	1450 mm	1450 mm	1450 mm	1450 mm
Minimum grapple diameter	85 mm	85 mm	85 mm	85 mm
Width of grapple	290/340 mm	290/340 mm	290/340 mm	290/340 mm
Weight, grapple + rotator	190 kg	190 kg	190 kg	190 kg

Gripto 608 | 609 | 708 | 709

» FOREST CRANE

GRIPTO 608 and 609 as well as 708 and 709 are easy to operate and a perfect supplement to our largest cranes Gripto 1009 and Gripto 1010. The Gripto 700 series is available with Smart Boom Control (crane tip control), which makes the control easier than ever. Gripto offers well-protected hoses inside the second boom all the way to the rotator. The hose dimension is also big enough to get maximal speed with minimum pressure losses.

» FEATURES

- Phenomenal precision and fast movements.
- Electronic end damping on the extensions (700 series), optional (600 series).
- Protected hoses inside the outer boom and out to the rotator.
- Smart Boom Control, optional (700 series).
- Lift and slewing dampers (700-series).

