

Quality since 1914

CHAIN MULCHERS | EXTENDO 610



EXTENDO 610

)) EFFICIENT CHAIN MULCHER

Kronos **EXTENDO 610** boom mulcher comes with a reach of 6,1 meters. Extendo consists of the previously seen **PREDATOR 1700H** mulcher head, a boom with long reach and an integrated hydraulic circuit for the mulcher head. The boom can be operated with the tractors own hydraulics or **LTCRA-NE**-control system that can be added as additional equipment. The parallel operation of the boom and cutting head makes the operation easy and stable.

)) FEATURES

- Integrated hydraulic circuit with oil tank and cooler. 70kw power (380bar).
- A reach of 6,1 meters from the center of the tractor.
- Parallell operation of boom and cutting head.
- Tilt on cutting head.
- Hydraulic operated front hood.
- Two-way collision protection, pressure accumulator on boom and spring mechanism on cutting head allowing the cutting head to move backwards and upwards in case of a collision.
- Replaceable skids made from Hardox steel.
- Tool hos
- Boom geometry designed to keep the cutting head forward for better ergonomics.
- · Optimized shape of the cutting head.

TECHNICAL INFORMATION

EXTENDO 610

Weight	2200 kg	Required amount of double acting sections, with free return	
Working width	1700 mm	Without LtCrane-steering system	4 pcs
PTO PTO	750–850 rpm	With LtCrane	1 pcs
Outreach from the longitudinal axis of the tract	or 6100 mm	With LtCrane , without Power Beyond	2 pcs
Recommended weight of tractor	6500 kg and more		

OPTIONAL EQUIPMENT

- 4-section valve for boom movements. Easily operated by right hand. Connected to the Power Beyond-outlet on the tractor. (Possible to connect to double acting outputs if desired.)
- 3-point lock system. Makes the lift-arms on smaller tractors more stable which makes working more precise and helps to reduce the load on the lift arms. The 3-point lock can be retrofitted.







